



SGT08 Waterproof

GPS Vehicle Tracker



Vehicle battery protection

Never drain out of the battery of motorcycle for optimal protection



IP65 dust and water proof

Water-resistant to ensure stable operation in tough environment



Remote cut-off (petrol/power)

Compel the vehicle to stop by breaking off the fuel connection



9-90V voltage range

Wide operating voltage applicable to all types of vehicles



SOS button

Thumb sized button allowing urgent call during an emergency case



Multiple alarms

Instant alert for vibration, overspeed, power off, geo-fence



Tracked by: SMS, APP, Web

Report location in real time through different interfaces

Application



Yacht



Vehicle tracking



Motorcycle



GSM Specification

| | |
|---------------------|---|
| GSM frequency | 850/900/1800/1900 MHz |
| GPRS | Class 12, TCP/IP |
| Memory | 32+32Mb |
| Phase error | RMSPE<5,PPE<20 |
| Max output | GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm |
| Max frequency error | ±0.1ppm |

GPS Specification

| | |
|-------------------------|---|
| GPS chipset | MTK high sensitivity chip |
| Frequency | L1, 1575.42MHz C/A code |
| GPS channel | 66 |
| Location accuracy | <10 meters |
| Tracking sensitivity | -165dBm |
| Acquisition sensitivity | -148dBm |
| TTF (open sky) | Avg. hot start ≤1sec Avg. cold start ≤35sec |

Function & Package

| | |
|-------------------------|--------------------------------|
| Dust water proof level | IP65 |
| Battery | 450mAh/3.7V Li-Polymer battery |
| Working voltage/current | 9-90VDC/7mA(60VDC) |
| Standby time | 70 hours |
| Working time | 5 hours |
| Operating temperature | -20°C~70°C |

İçerenköy Mah. Necmettin Erbakan Cad. Özce Yılmaz İş Mrk. No:97 K:4 D:19 Ataşehir/İstanbul
Tel: +90(850)5322578 - +90(216)6613844-45 Fax: +90(216)6613843
info@satlink.com.tr / www.satlink.com.tr